



GENERAL

Transmitter Type

FM Broadcast, 100% solid state

Configuration

Two V1 FM Broadcast transmitters combined using one VC2.5 combiner module

RF Output Power

60 W to 2,800 W into a 1.2 VSWR

60 W to 2,500 W into a 1.5 VSWR

RF Output Connection

7/8" EIA, female

(7/16" DIN available)

RF Output Impedance

50 ohms unbalanced

Efficiency

60% typical at 2,500 W

RF Load VSWR

1.5:1 - Automatic power reduction into higher VSWR

Protected from open and short circuits at all phase angles

RF Frequency Range

87.5 MHz to 108 MHz

No tuning required

Turn Around Loss

Better than 11 dB

Excitation

FM Exciter capable of 35 W (minimum)

45 W (recommended)

Spurious and Harmonic

Meets or exceeds all FCC/IC requirements

AC INPUT

Voltage

180 V ac to 264 V ac, 1 phase, 50/60 Hz

Power Consumption

4.17 kW at 2.5 kW RF output (4.21 kVA)

Power Factor

Unity Power Factor Corrected (typically 0.99)

Power Line Harmonics

IEEE 519-1992

AUDIO PERFORMANCE

Asynchronous AM S/N Ratio

Better than 60 dB below reference carrier with 100% amplitude modulation using 75 μ s de-emphasis (no FM modulation present)

Synchronous AM S/N Ratio

Better than 50 dB below reference carrier with 100% amplitude modulation 75 μ s de-emphasis

ENVIRONMENTAL

Temperature Range

0°C to +50°C

Derate 3°C per 500 m above sea level

(2°C per 1,000 ft)

Humidity Range

0% to 95% non-condensing

Altitude

0 m to 3,000 m (0 ft to 10,000 ft)

Cooling Air Requirements

263m³/hr (154 cfm)

PHYSICAL

Dimensions

Open ventilation configuration:

W = Standard 19" (48.3 cm) EIA rack
[minimum opening of 17.5" (44.5 cm)]

H = 9 RU = 15.75" (40.0 cm)

D = Dependent upon connector type (not including handles)

7/16 DIN = 21.5" (54.6 cm)

7/8 EIA = 22.4" (56.9 cm)

Weight

43.6 kg (96.1 lbs)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.