

## GENERAL

### Transmitter Type

FM Broadcast, 100% solid state

### Configuration

24 hot swappable RF power modules

48 switching power supplies (2 per RF power module)

Power supplies are hot-swappable

2 low voltage power supplies (same as RF power module power supply) with 2 redundant supplies standard

Integrated exciter

Remote Interface PWB

### Optional

Main/standby exciter

UPS Interface

Orban Inside

Additional LVPS

### RF Output Connection

4-1/16 inch EIA, female (standard)

6-1/8 inch EIA, female (optional)

### RF Output Impedance

50 ohms unbalanced

### RF Load VSWR

1.5:1 with automatic power reduction into higher VSWR

Protected from open and short circuits at all phase angles

### RF Frequency Range

87.5 MHz to 108 MHz

No tuning required

### Frequency Stability

± 200 Hz

### Turn Around Loss

Better than 20 dB

### Spurious and Harmonic

Meets or exceeds all FCC/IC/RED requirements

## AC INPUT

### Voltage (factory configured)

Dual input standard (single input optional)

208 Vac nom. 3-ph. or 240 Vac nom. 1-ph. (90 Vac to 265 Vac with reduced output power capability below 175 Vac)

380 Vac nom. 3-ph. (156 Vac to 459 Vac with reduced output power capability below 303 Vac)

47-66 Hz

Bottom AC input optional; factory configurable; contact Nautel for details

### Power Consumption

#### Analog Mode:

91.7 kW at 66 kW RF output (93.5 kVA)

#### HD Radio Hybrid Mode (-20dB):

85.7 kW at 60 kW RF output (87.5 kVA)

#### HD Radio Hybrid Mode (-14dB):

90 kW at 54 kW RF output (91.8 kVA)

#### HD Radio Hybrid Mode (-10dB):

72.7 kW at 40 kW RF output (74.2 kVA)

### Power Factor

Unity Power Factor Corrected (typically 0.98)

### Power Line Harmonics

IEEE 519-1992



### RF Output Power and Efficiency

	Analog Mode (max/rated)	HD Radio Hybrid (-20dB)	HD Radio Hybrid (-14dB)	HD Radio Hybrid (-10dB)
<b>Analog TPO (kW)</b>	<b>66 / 60</b>	<b>60</b>	<b>54</b>	<b>40</b>
<b>Typical Efficiency</b>	<b>72%</b>	<b>70%</b>	<b>60%</b>	<b>55%</b>

Typical analog power measured with MP3 mode, 1.1:1 VSWR.

Power outputs vary with injection level, frequency, VSWR, MP operating mode, and symmetrical vs. asymmetrical sidebands. Please contact your Nautel representative to discuss your specific HD power requirement.

## AUDIO PERFORMANCE

### Asynchronous AM S/N Ratio

Better than 60 dB below reference carrier with 100% amplitude modulation using 75  $\mu$ s de-emphasis (no FM modulation present)

### Synchronous AM S/N Ratio

Better than 50 dB below reference carrier with 100% amplitude modulation using 75  $\mu$ s de-emphasis

## ENVIRONMENTAL

### Temperature Range

0°C to +50°C  
Derate 3°C per 500 m above sea level  
(2°C per 1000 ft)

### Humidity Range

0% to 95% non-condensing

### Altitude

0 m to 3000 m (0 ft to 10,000 ft)

### Cooling Air Requirements

8326 m<sup>3</sup>/hr (4900 cfm)

## COMPLIANCE

Product complies with:

- ISED specification BETS6 issue 2
- FCC CFR title 47 part 2 and part 73
- Conforms with all essential requirements of Radio European Directive 2014/53/EU

## PHYSICAL

### Dimensions

Open ventilation configuration:  
184.2 cm H x 259 cm W x 83.8 cm D  
(72.5" H x 102" W x 33" D)

Note: total depth can be reduced to 76.2 cm (30") with rear filter panels and front doors removed.

Closed ventilation configuration - consult factory

Single cabinet standard (separated racks optional)

Custom combiner orientation and reject load position available

Contact your Nautel representative to discuss any custom requirements

### Weight

1147 kg (2530 lbs) cabinet and combiner (excluding reject load typ. 62 kg (136 lbs)), all uncrated weights